

## AMENDMENT TO THE CLAIMS

The amendments set forth below to the claims replace all other prior amendments to the claims.

1. (Cancelled).
2. (Cancelled).
3. (Cancelled).
4. (Cancelled).
5. (Cancelled).
6. (Cancelled).
7. (Cancelled).
8. (Cancelled).
9. (Cancelled).
10. (Cancelled).
11. (Presently Amended) An RFID encoding/verifying apparatus comprising:
  - a platform for positioning RFID containing stock upon;
  - a feeder positioned on said platform for advancing said RFID containing stock;

- a motor in communication with said feeder for advancing said RFID containing stock a predetermined distance when activated;
- an RFID read/write unit comprising at least one antenna with read/write capability for transmitting information to said RFID containing stock as said RFID containing stock is advanced past said RFID read/write unit;
- at least one antenna with read/write capability for transmitting information to RFID containing stock as said RFID containing stock is advanced past said at least one antenna;
- at least one barcode reader positioned on said platform so as to read information from said RFID containing stock as said RFID containing stock is advanced passed said barcode reader and wherein the at least one barcode reader is in communication with said processor and said barcode reader reads said barcodes on said RFID containing stock and sends information to said processor to be verified;
- a processor in communication with said motor and said RFID read/write unit, said processor controlling the advancing of said motor and the transmission of data to and from said RFID read/write unit;
- a radio frequency driver in communication with said processor, said radio frequency driver configured so as to send signals to said RFID read/write unit for transmission to said RFID containing stock; and

a marking unit in communication with said processor wherein said marking unit perforates designs in said RFID containing stock when activated

~~The RFID encoding/verifying apparatus according to claim 10 wherein said marking unit perforates designs in said RFID containing stock when activated.~~

12.(Presently amended) The RFID encoding/verifying apparatus according to claim 11 ~~4~~ wherein the feeder is either tractor fed or non-tractor fed.

13.(Previously amended) The RFID encoding/verifying apparatus according to claim 12 wherein the feeder is attached to an adjustable track and said feeder can be adjusted to accommodate RFID containing stock of various widths.

14. (Presently Amended) The RFID encoding/verifying apparatus according to claim 11 ~~7~~ wherein at least part of the platform is transparent and said barcode reader is positioned directly below said transparent portion of said platform.

15. (Presently Amended) The RFID encoding/verifying apparatus according to claim 11 8 wherein at least part of the platform is transparent and said OCR scanner is positioned directly below said transparent portion of said platform.

16. (Presently Amended) The RFID encoding/verifying apparatus according to claim 11 7 wherein said barcode reader is attached to said platform by an adjustable arm that can accommodate RFID containing stock of various widths.

17. (Presently Amended) The RFID encoding/verifying apparatus according to claim 11 8 wherein said OCR scanner is attached to said platform by an adjustable arm that can accommodate RFID containing stock of various widths.

18. (Presently Amended) The RFID encoding/verifying apparatus according to claim 11 7 wherein said barcode reader is for reading barcodes of various widths.

19. (Presently Amended) The RFID encoding/verifying apparatus according to claim 11 + wherein the motor is a stepper motor.

20. (Original) The RFID encoding/verifying apparatus according to claim 19 further comprising a stepper motor driver in communication with said processor whereby said controller converts a digital signal received from said controller to a pulse signal and relays said pulse signal to said stepper motor driver so as to drive said stepper motor accordingly.

21. (Presently Amended) The RFID encoding/verifying apparatus according to claim 11 + further comprising an adjustable forward RFID containing stock roller for roll or non-printed fan-folded stock positioned at one end of said platform.

22.(Original) The RFID encoding/verifying apparatus according to claim 21 wherein said forward RFID containing stock roller is self adjusting whereby said forward RFID containing stock roller automatically adjusts its width so as to accommodate said width of said RFID containing stock.

23. (Original) The RFID encoding/verifying apparatus according to claim 22 further comprising a receiving roller for roll RFID containing stock positioned at the end directly opposite said forward RFID containing stock roller.

24. (Original) The RFID encoding/verifying apparatus according to claim 11 ~~12~~ comprising an attachment located at opposite ends of said platform for feeding and receiving fan-fold RFID containing stock.

25. (Presently Amended) A method for encoding/verifying RFID containing stock using the RFID containing stock encoding/verifying apparatus according to claim 11 ~~10~~ comprising;

- positioning said RFID containing stock in said feeder on said platform of said RFID encoding/verifying apparatus;
- advancing said RFID containing stock using said motor to position at least one RFID containing stock unit in communication with said RFID read/write unit;
- reading said information on said RFID containing stock using said read/write RFID unit and communicating said data to said processor;

- scanning said barcode and communicating said information to said processor;
- generating at least one program instruction by said processor in response to comparing said RFID tag information and said barcode information by said processor;
- said program instructions selected from the group consisting of instructing said read/write unit to write specific information to said RFID containing stock, activating said marking unit to mark said RFID containing stock, and advancing said motor so as to repeat said process.

26. (Original) The method according to claim 25 wherein an OCR is used in place of said barcode scanner.

27. (Original) The method according to claim 25 wherein clinical labels are produced.

28. (Original) The method according to claim 25 wherein non-clinical labels are produced.

29.(Original) The method according to claim 25 wherein blank RFID containing stock is used.

30. (Original) The RFID encoding/verifying apparatus according to claim 14 further comprising two retractable shutters positioned on opposite sides of the transparent portion of the platform enabling the widening and narrowing of the transparent portion of the platform.

31. (Presently Amended) The RFID encoding/verifying apparatus according to claim 11 7 wherein one barcode reader is in a different orientation than a second barcode reader.

32. (Original) The RFID encoding/verifying apparatus according to claim 14 further comprising a cycling belt positioned around said platform and in communication with said motor for moving said RFID containing stock in a predetermined direction.

33. (Presently Amended) The RFID encoding/verifying apparatus according to claim 11 4 further comprising an optical sensor in communication with



said motor, said optical sensor controlling the advancing of said motor according to data gathered by said optical sensor.

34. (Presently Amended) The RFID encoding/verifying apparatus according to claim 11 + further comprising an optical sensor in communication with said processor, said processor sending RFID commands to read and/or write data from/to a tag embedded in a stock unit once a signal is sent from said optical sensor to said processor.

35. (Previously Presented) An RFID encoding/verifying apparatus comprising:

- a platform for positioning RFID containing stock upon;
  - a feeder positioned on said platform for advancing said RFID containing stock;
  - a motor in communication with said feeder for advancing said RFID containing stock a predetermined distance when activated;
  - an RFID read/write unit comprising at least one antenna with read/write capability for transmitting information to said RFID containing stock as said RFID containing stock is advanced past said RFID read/write unit;

- a processor in communication with said motor and said RFID read/write unit, said processor controlling the advancing of said motor and the transmission of data to and from said RFID read/write unit;
- a marking unit in communication with said processor whereby said marking unit perforates said RFID containing stock when activated; and
- a feeder attached to an adjustable track wherein said feeder can be adjusted to accommodate RFID containing stock of various widths.

36. (Previously Presented) The RFID encoding/verifying apparatus according to claim 35 wherein the feeder is either tractor fed or non-tractor fed.

37.(Previously Presented) The RFID encoding/verifying apparatus according to claim 36 wherein the feeder is attached to an adjustable track and said feeder can be adjusted to accommodate RFID containing stock of various widths.

38.(Previously Presented) The RFID encoding/verifying apparatus according to claim 35 wherein the read/write unit comprises at least one integrated circuit coupled to at least one antenna with read/write capability for

transmitting information to RFID containing stock as said RFID containing stock is advanced past said at least one antenna; and  
said RFID encoding/verifying apparatus further comprises at least one barcode reader positioned on said platform so as to read information from said RFID containing stock as said RFID containing stock is advanced passed said barcode reader.

39. (Previously Presented) The RFID encoding/verifying apparatus according to claim 38 wherein said barcode reader is positioned directly below said transparent portion of said platform.

40. (Previously Presented) The RFID encoding/verifying apparatus according to claim 35 wherein the read/write unit comprises at least one integrated circuit coupled to at least one antenna with read/write capability for transmitting information to RFID containing stock as said RFID containing stock is advanced past said at least one antenna; and  
said RFID encoding/verifying apparatus further comprising an OCR scanner positioned on said platform so as to read information from said RFID containing stock as said RFID containing stock is advanced passed said OCR scanner.

41. (Previously Presented) The RFID encoding/verifying apparatus

according to claim 40

wherein at least part of the platform is transparent and said OCR scanner is positioned directly below said transparent portion of said platform.

42. (Previously Presented) The RFID encoding/verifying apparatus

according to claim 38 wherein said barcode reader is attached to said

platform by an adjustable arm that can accommodate RFID containing stock of various widths.

43. (Previously Presented) The RFID encoding/verifying apparatus

according to claim 40 wherein said OCR scanner is attached to said platform

by an adjustable arm that can accommodate RFID containing stock of various widths.

44. (Previously Presented) The RFID encoding/verifying apparatus

according to claim 38 wherein said barcode reader is for reading barcodes of various widths.

45. (Previously Presented) The RFID encoding/verifying apparatus according to claim 35 wherein the motor is a stepper motor and said RFID encoding/verifying apparatus further comprises a stepper motor driver in communication with said processor whereby said controller converts a digital signal received from said controller to a pulse signal and relays said pulse signal to said stepper motor driver so as to drive said stepper motor accordingly.

46. (Previously Presented) The RFID encoding/verifying apparatus according to claim 36 further comprising an adjustable forward RFID containing stock roller for roll or non-printed fan-folded stock positioned at one end of said platform.

47. (Previously Presented) The RFID encoding/verifying apparatus according to claim 46 wherein said forward RFID containing stock roller is self adjusting whereby said forward RFID containing stock roller automatically adjusts its width so as to accommodate said width of said RFID containing stock.

48. (Previously Presented) The RFID encoding/verifying apparatus according to claim 47 further comprising a receiving roller for roll RFID containing stock positioned at the end directly opposite said forward RFID containing stock roller.

49. (Previously Presented) The RFID encoding/verifying apparatus according to claim 36 comprising an attachment located at opposite ends of said platform for feeding and receiving fan-fold RFID containing stock.

50. (Previously Presented) The RFID encoding/verifying apparatus according to claim 39 further comprising two retractable shutters positioned on opposite sides of the transparent portion of the platform enabling the widening and narrowing of the transparent portion of the platform.

51. (Previously Presented) The RFID encoding/verifying apparatus according to claim 38 wherein one barcode reader is in a different orientation than a second barcode reader.

52. (Previously Presented) The RFID encoding/verifying apparatus according to claim 39 further comprising a cycling belt positioned around

said platform and in communication with said motor for moving said RFID containing stock in a predetermined direction.

53. (Previously Presented) The RFID encoding/verifying apparatus according to claim 35 further comprising an optical sensor in communication with said motor, said optical sensor controlling the advancing of said motor according to data gathered by said optical sensor.

54. (Previously Presented) The RFID encoding/verifying apparatus according to claim 35 further comprising an optical sensor in communication with said processor, said processor sending RFID commands to read and/or write data from/to a tag embedded in a stock unit once a signal is sent from said optical sensor to said processor.